



fitted with

- work equipment**
- connected load**
- power consumption**
- power factor**
- luminous flux**
- luminous efficacy**
- light distribution**
- direct ratio**
- light colour**
- color rendering index (CRI)**
- glare-free**
- luminance**
- unified glare rating**
- technology**
- usage**
- luminaire body**
- lamp cover**
- tubular section**
- weight (net)**
- mains lead**
- fastening**
- decorative contrast side parts**
- special features**

- 3 x LED module
- light colour adjustable white
- Energy efficiency category A
- 2 x LED module
- light colour neutral white
- Energy efficiency category A+
- power supply unit
- 220-240V; 50/60Hz
- approx. 94 W
- approx. 0,966
- approx. 11500 lm
- approx. 122 lm/W
- direct/indirect
- approx. 17 %
- adjustable white
- > 80
- conical prismatic screen
- < 2800 cd/m²
- < 16
- controlled depending on presence and daylight
- multi-function switch
- steel/plastic, painted, white
- polycarbonate, clear
- steel tube, painted, tubular section upright, white
- approx. 8.3 kg
- approx. 3,7 m; mains plug
- CEE 7/II
- table adaptor
- flint grey
- luminaire head detachable, integrated light- and presence-detecting sensor PULSE, integrated light management for biodynamic light PULSE VTL, light forming, retrofit with EnOcean wireless module PULSE-TALK, inclination of tubular section adjustable



CEE 7/II

luminous intensity

